

# The power of Infini8

Technical features

'Ashta' or Eight is a powerful number; it represents infinity. The two circles that form an '8' have no beginning or end; they merge into one infinite unit. TechnoSLAB has a distinct character propelled with eight powers. We call it the Power of Infini8.



UV & HEAT RESISTANT



STAIN RESISTANT



SCRATCH & ABRASION RESISTANT



WATER RESISTANT



CHEMICAL RESISTANT



HYGIENIC SURFACE



DIMENSIONAL STABILITY



FROST RESISTANT

Technical features 22 - 23

# Explore the unexplored



Discover a spree of color sprinkled on white marble slabs as you go deep diving for your best match into the Marble series.

# Living room

From casual conversation to entertainment, the living room is where memories are made. Elegance and sophistication in your space that reflects your style.



Blackgold Travertine

2400x1200mm *Lustrous* 

→ 9 mm Thickness

Floor

Antique Botticino

2400x1200mm *Lustrous* 

\chi 9 mm Thickness



Timber Bruno

2400x1200mm *Mute* 

→ 6 mm Thickness

Steps

Blackgold Travertine

2400x1200mm *Lustrous* 

→ 9 mm Thickness

Riser

Antique Botticino

2400x1200mm *Lustrous* 

→ 9 mm Thickness







### Antique Botticino

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 2





1200x1200mm Lustrous 9 mm 4 Faces



### Marble series

# Blackgold Travertine

2400x1200mm

Lustrous / Orgatech

9 mm Thickness

Total faces - 2



O2.1 Marble series 32 - 33

# Leisure Area

Nothing like a breath of fresh air and cup of tea in your leisure time is the simplest way of bringing your space to life. From the marble series giving rich feel of Natural Stone available in earthy natural hues.



Wall

Armani Grey

2400x1200mm Crystalline



→ 9 mm Thickness

Artistic Wall

Armani Gold

1200x1200mm Crystalline




→ 9 mm Thickness

Floor

Armani Gold

1200x1200mm *Lustrous* 

→ 9 mm Thickness



02.1 Marble series



1200x1200mm

9 mm

5 Faces

Lustrous / Satin

#### Marble series

### Armani Grey

2400x1200mm

Lustrous / Crystalline / Satin

9 mm Thickness





#### Color Options

Armani Gold


2400x1200mm 1200x1200mm Lustrous / Satin 9 mm 3 Faces

Armani Brown



2400x1200mm 1200x1200mm Lustrous 9 mm 3 Faces





### Marble series

### Camoflague Esperada

2400x1200mm

Lustrous


9 mm Thickness

Total faces - 3













1600x1600mm Crystalline 9 mm 5 Faces

### Antique Grey






3200x1600mm

Crystalline

9 mm Thickness







### Marble series

# Statuario Unico

#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

Total faces - 3





2400x1200mm Lustrous / Crystalline / Satin 6 mm, 9 mm 3 Faces



1600x1600mm Crystalline / Satin 9 mm 6 Faces

02.1 Marble series 38 - 39



# Waiting Area

The wait can't get any longer. Fascinating and elegant tile options can create a huge swathe effect to your waiting area.



# Carrara Ultimo

2400x1200mm Crystalline

★ 6 mm Thickness

Carrara Ultimo

2400x1200mm Crystalline

★ 6 mm Thickness



#### Astonia Grey

2400x1200mm Crystalline



→ 9 mm Thickness

#### Steps

#### Astonia Grey

2400x1200mm *Crystalline* 


→ 9 mm Thickness


#### Floor

#### Carrara Ultimo

2400x1200mm Crystalline

→ 9 mm Thickness








### Carrara Ultimo

#### 3200x1600mm

#### Crystalline / Satin

- → 6 mm Thickness
- 9 mm Thickness
- 12 mm Thickness

Total faces - 3





2400x1200mm Lustrous / Crystalline 6 mm, 9 mm 3 Faces



1600x1600mm Crystalline 9 mm 6 Faces



#### Marble series

### Carrara

#### 3200x1600mm

#### Crystalline / Satin

- → 6 mm Thickness
- 9 mm Thickness
- 12 mm Thickness

Total faces - 2










1600x1600mm Crystalline 9 mm 4 Faces

02.1 Marble series 44 - 45



### **Everest White**

3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness



12 mm Thickness

1200x1200mm

Lustrous/Mute

9 mm

2400x1200mm

Lustrous / Satin

6 mm, 9 mm, 12 mm

1600x1600mm Crystalline / Satin

9 mm



#### Marble series



#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness







2400x1200mm Lustrous 9 mm 3 Faces





# Arabescato Statuario

2400x1200mm

Lustrous / Crystalline

9 mm Thickness

Total faces - 3





### Marble series

### Statuario Bianco

2400x1200mm

Lustrous / Crystalline

9 mm Thickness

Total faces - 4









1200x1200mm Lustrous 9 mm 8 Faces

02.1 Marble series 48 - 49



### Statuario


#### 3200x1600mm

#### Crystalline

★ 6 mm Thickness

9 mm Thickness

12 mm Thickness









2400x1200mm Lustrous 9 mm 3 Faces



1600x1600mm Crystalline 9 mm 6 Faces



#### Marble series

### Apuane Statuario

#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness







2400x1200mm Lustrous / Crystalline / Satin 6 mm, 9 mm 2 Faces



1600x1600mm Crystalline 9 mm 4 Faces



1200x1200mm Lustrous 9 mm 4 Faces

02.1 Marble series 50 - 51



# Calacutta Borghini

#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

Total faces - 3





2400x1200mm Lustrous / Crystalline / Satin 6 mm, 9 mm 12 mm 3 Faces



1600x1600mm Crystalline 9 mm 6 Faces



#### Marble series

### Statuario Platina

### 3200x1600mm

#### Crystalline / Satin


→ 6 mm Thickness

9 mm Thickness

12 mm Thickness



Continue Faces









1200x1200mm Lustrous / Satin 9 mm 6 Faces

02.1 Marble series 52 - 53



### Statuario Venato

#### 3200x1600mm

#### Crystalline / Satin

★ 6 mm Thickness

9 mm Thickness

12 mm Thickness







1600x1600mm Crystalline 9 mm 4 Faces



#### Marble series

# Statuario Venetian

#### 2400x1200mm

#### Lustrous / Crystalline / Satin


→ 6 mm Thickness

9 mm Thickness









02.1 Marble series 54 - 55



# Luxurious Bathroom

Tiles that spell splendour for the enigmatic and enormous commercial bathroom area. The aesthetic designs make a mark for their own.

Wall - 1

Silver River

2400x1200mm *Lustrous* 

→ 9 mm Thickness

Wall - 2

Calacutta Bianco Oro

2400x1200mm Crystalline

→ 9 mm Thickness

Wall - 3

Calacutta Bianco Oro

2400x1200mm *Crystalline* 

→ 9 mm Thickness

Floor

Silver River

2400x1200mm *Lustrous* 

→ 9 mm Thickness

Bathtub

Calacutta Bianco Oro

2400x1200mm *Lustrous* 

💥 9 mm Thickness





# Calacutta Bianco Oro

#### 3200x1600mm

#### Crystalline

★ 6 mm Thickness

9 mm Thickness

12 mm Thickness

Total faces - 3







2400x1200mm Lustrous / Crystalline 9 mm 3 Faces



1600x1600mm Crystalline 9 mm 5 Faces



#### Marble series

### Celio



#### 3200x1600mm

#### Crystalline



12 mm Thickness

Total faces - 2





1600x1600mm Crystalline 9 mm 6 Faces

02.1 Marble series 58 - 59



### Botticino Fiorito

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 2





1200x1200mm Lustrous 9 mm 4 Faces



#### Marble series

### Bronze Armani



#### Crystalline / Satin













1600x1600mm Crystalline 9 mm 5 Faces

02.1 Marble series 60 - 61



### Breccia

3200x1600mm

Crystalline

9 mm Thickness







2400x1200mm Lustrous 9 mm 4 Faces



1600x1600mm Crystalline 9 mm 4 Faces



1200x1200mm Lustrous 9 mm 4 Faces



### Marble series

### Breccia Nuvo

2400x1200mm

Lustrous

9 mm Thickness







1200x1200mm Lustrous / Satin 9 mm 4 Faces

02.1 Marble series 62 - 63



### Breccia Blue

2400x1200mm

Lustrous

9 mm Thickness







### Marble series

# Dolce Grey

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 2



O2.1 Marble series 64 - 65



### Classic Beige

3200x1600mm

Crystalline

9 mm Thickness

Total faces - 3





2400x1200mm Lustrous 9 mm 3 Faces



1600x1600mm Crystalline 9 mm 6 Faces



1200x1200mm Lustrous 9 mm 6 Faces



#### Marble series

# Burberry Beige

3200x1600mm

Crystalline

9 mm Thickness

Total faces - 2









1600x1600mm Crystalline 9 mm 4 Faces

02.1 Marble series 66 - 67





### Omani

2400x1200mm

Lustrous

9 mm Thickness








1200x1200mm Lustrous 9 mm 6 Faces





### Regal Beige

2400x1200mm

Lustrous / Crystalline

9 mm Thickness





1200x1200mm Lustrous 9 mm 6 Faces

02.1 Marble series 68 - 69



### Bathroom

The residential bathrooms space can be crafted with our massive tile collection creating an incredibly calming effect.



#### Emperador Classic

1200x1200mm *Lustrous* 

→ 9 mm Thickness

#### Wall - 2

#### Emperador Light

1200x1200mm *Lustrous* 

→ 9 mm Thickness

#### Floor

Emperador Light

1200x1200mm Lustrous

→ 9 mm Thickness

Basin Table

Emperador Light

1200x1200mm *Lustrous* 

🛨 9 mm Thickness





### Emperador Light

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 4





1200x1200mm Lustrous 9 mm 4 Faces



### Marble series

### Emperador Classic

2400x1200mm

Lustrous

9 mm Thickness







1200x1200mm Lustrous 9 mm 4 Faces

02.1 Marble series 72 - 73



### Dyna Classic

2400x1200mm

Lustrous

9 mm Thickness







### Marble series

### Grigio Nuvolato

2400x1200mm

Lustrous / Crystalline

9 mm Thickness

Total faces - 2





1200x1200mm Lustrous 9 mm 4 Faces



1200x1200mm Lustrous 9 mm 4 Faces

02.1 Marble series 74 - 75



### Irish Brown

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 2





### Marble series

### Silver River

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 3







### Serpegiente Italy


2400x1200mm

Lustrous

9 mm Thickness

Total faces - 3







#### Marble series

### Travertine Beige

2400x1200mm

Lustrous / Mute

→ 6 mm Thickness

9 mm Thickness

Total faces - 2





1200x1200mm Lustrous/Satin 9 mm 4 Faces

02.1 Marble series 78 - 79



# Hotel Reception

Our large format slabs are an ideal solution to enhance the beauty and grandeur of every hotel reception with our intriguing designs and patterns.

Wall - 1

Celio

3200x1600mm Crystalline

→ 9 mm Thickness

Wall - 2

Etnico

3200x1600mm Crystalline

→ 9 mm Thickness

Floor

Etnico

3200x1600mm Crystalline

→ 9 mm Thickness


Table

Etnico

3200x1600mm Crystalline

\chi 9 mm Thickness





Wall - 1

Celio

3200x1600mm *Crystalline* 

\chi 9 mm Thickness

Floor

Etnico

3200x1600mm *Crystalline* 

→ 9 mm Thickness



02.1 Marble series 82 - 83



### Etnico



3200x1600mm

Crystalline

9 mm Thickness

Total faces - 3





### Marble series



2400x1200mm

Lustrous

9 mm Thickness

Total faces - 2





1200x1200mm Lustrous/Satin 9 mm 4 Faces

02.1 Marble series 84 - 85



### Pulpis Grey

3200x1600mm

Crystalline

9 mm Thickness

Total faces - 3





1600x1600mm Crystalline 9 mm 4 Faces



#### Marble series

# Pietra Grey

### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness









2400x1200mm Lustrous / Crystalline / Satin 9 mm 3 Faces




1600x1600mm Crystalline 9 mm 5 Faces



86 - 87

1200x1200mm Lustrous 9 mm 5 Faces



# **Luxury Store**

Style never takes a day off. Lightning striking on our grey tile. Combining our marble and stone is our glamour's product take on a perfect 'Show Stopper'

Floor

Astonia Grey

2400x1200mm *Lustrous* 

→ 9 mm Thickness



### Astonia Grey



#### Crystalline / Mute

★ 6 mm Thickness

9 mm Thickness

12 mm Thickness







2400x1200mm Lustrous / Crystalline 9 mm 3 Faces



1600x1600mm Crystalline 9 mm 6 Faces





### Marble series

### Nordic Grey

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 2





1200x1200mm Lustrous 9 mm 6 Faces


02.1 Marble series 90 - 91



#### Crystalline / Satin

9 mm Thickness







1600x1600mm Crystalline 9 mm 6 Faces

### Nero Marquina

#### 3200x1600mm

→ 6 mm Thickness

12 mm Thickness







### Marble series


### Marquina Venatino


2400x1200mm

Lustrous / Crystalline

9 mm Thickness


Total faces - 3





1200x1200mm Lustrous 9 mm 4 Faces

02.1 Marble series 92 - 93



### Black Flash

3200x1600mm

#### Crystalline

9 mm Thickness

12 mm Thickness

Total faces - 2





### Marble series


### Black Fusion

3200x1600mm


Crystalline

9 mm Thickness

Total faces - 3



02.1 Marble series 94 - 95



# White Santorini


3200x1600mm

Crystalline

9 mm Thickness

Total faces - 3





1600x1600mm Crystalline 9 mm 6 Faces



### Marble series

### Crema Atlantico

1200x1200mm

Lustrous

9 mm Thickness





02.1 Marble series 96 - 97

# Explore the unexplored



Terrazzo is the latest interior trend and is here to stay. The terrazzo series creates a nostalgic mosaic patterns and is available in Beige and Grey shade options.



## Sauna Spa

A space that inspires tranquillity and largeness required for the sauna and spa can be crafted from the soothing colour range we offer for the wide tiles.

Wall - 1

Cemento Flakes

1200x1200mm *Mute* 

→ 9 mm Thickness

Wall - 2

Cemento Flakes

1200x1200mm *Mute* 

→ 9 mm Thickness

Wall - 3

Tuscan Chips


2400x1200mm *Mute* 

→ 9 mm Thickness

Floor


Tuscan Chips

2400x1200mm *Mute* 





02.2 Terrazzo series 102 - 103



Wall - 1

Cemento Flakes

1200x1200mm *Mute* 

→ 9 mm Thickness

Wall - 2

Cemento Flakes

1200x1200mm *Mute* 

→ 9 mm Thickness

Wall - 3

Tuscan Chips

2400x1200mm *Mute* 

→ 9 mm Thickness

Floor

Tuscan Chips

2400x1200mm *Mute* 

→ 9 mm Thickness



### Tuscan Chips

2400x1200mm

Mute

9 mm Thickness







1200x1200mm Mute 9 mm 4 Faces

02.2 Terrazzo series 104 - 105



### Terrazzo series

## Cemento Flakes

3200x1600mm

#### Mute

9 mm Thickness



Total faces - 2





1200x1200mm Mute 9 mm, 12 mm 4 Faces



Terrazzo series

## Beton Flakes Grey

### Mute

9 mm Thickness



3200x1600mm








1200x1200mm Mute 9 mm 4 Faces

02.2 Terrazzo series 106 - 107

# Explore the unexplored



Scout into our stone series as it extracts the essence of nature with tiles as wide as the sky, you will be lost into the beauty of this journey.



### Stone series

### Ignazio

2400x1200mm

Lustrous / Mute

9 mm Thickness

Total faces - 3





### Stone series

### Mountain Latte

### 3200x1600mm

#### Mute

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

Total faces - 3





2400x1200mm Mute 6 mm, 9 mm 3 Faces

### Color Options Mountain Coin

Mountain Tortora



3200x1600mm 2400x1200mm Mute 6 mm, 9 mm 12 mm 3 Faces

3200x1600mm 2400x1200mm Mute 6 mm, 9 mm 12 mm 3 Faces

3600x1600mm 2400x1200mm Mute 6 mm, 9 mm 12 mm 3 Faces

02.3 Stone series 112 - 113



Hospitality

## Cafetaria

Coffee evokes a good mood, so unwind and 'EXPRESSO YOURSELF'

A time to take a break and enjoy warm ambience with the grandeur and colors splashed with our stone series adding cordial grunge to our industrial trendy interiors.

Wall

Nero Marquina

3200x1600mm *Crystalline* 

→ 6 mm Thickness

→ 9 mm Thickness

Floor

Ardesia Grigio

2400x1200mm *Mute* 

→ 9 mm Thickness

Bar Table / Platform

Statuario

3200x1600mm *Crystalline* 

 $\stackrel{\textstyle \ }{\raisebox{-4pt}{$\times$}}$  6 mm Thickness



### Stone series

### Ardesia Brown


### 2400x1200mm

#### Mute

★ 6 mm Thickness







#### Color Options



2400x1200mm Mute 6 mm, 9 mm 4 Faces 2400x1200mm Mute 6 mm, 9 mm 4 Faces 2400x1200mm Mute 6 mm, 9 mm 4 Faces 1200x1200mm

Mute

9 mm

6 Faces



### Stone series

### Arenisca Crema

#### 2400x1200mm

#### Mute

9 mm Thickness

Total faces - 3




#### Color Options

#### Arenisca Night



2400x1200mm 1200x1200mm Mute 9 mm 3 Faces

02.3 Stone series 116 - 117





### Stone series

### Pias Pearl

2400x1200mm

Mute

9 mm Thickness

Total faces - 3




#### Color Options

Pias Bronze



2400x1200mm Mute 9 mm 3 Faces

2400x1200mm Mute 9 mm 3 Faces



### Stone series

### Belgium Stone

3200x1600mm

#### Orgatech

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

Total faces - 2





1600x1600mm Orgatech 6 mm, 9 mm, 12 mm 4 Faces

02.3 Stone series 120 - 121

## Island Kitchen

A free flow space in your island kitchen interiors can be covered with our unmatched shades and design from our selective tile range which offers expanse and simplicity.

Floor

Seiser Slate

2400x1200mm *Mute* 

→ 9 mm Thickness

Kitchen Platform

Lithic Nero

2400x1200mm *Mute* 

 $\stackrel{\textstyle \times}{\raisebox{-1.5ex}{$\times$}}$  6 mm Thickness

Drawer

Timber Bruno

2400x1200mm *Mute* 

★ 6 mm Thickness

Dining Table

Timber Bruno

2400x1200mm *Mute* 

→ 6 mm Thickness



02.3 Stone series 122 - 123



Floor

Seiser Slate

2400x1200mm *Mute* 

→ 9 mm Thickness

Kitchen Platform

Lithic Nero

2400x1200mm *Mute* 

 $\stackrel{\textstyle \star}{\textstyle \star}$  6 mm Thickness

Drawer Timber Bruno

2400x1200mm *Mute* 

\chi 6 mm Thickness



### Stone series

### Seiser Coco

2400x1200mm

Mute

9 mm Thickness





Color Options

Seiser Slate



2400x1200mm 1200x1200mm Mute 9 mm 2 Faces



Mute

9 mm

4 Faces

02.3 Stone series 124 - 125



9 mm Thickness

#### Total faces - 4



#### Color Options

Castello Coin Castello Grigio Castello Antracite

1200x1200mm Mute 9 mm 4 Faces

1200x1200mm Mute 9 mm 4 Faces

1200x1200mm Mute

9 mm

4 Faces

### Stone series

### Castello Latte



1200x1200mm

Mute









### Avola Desert



1200x1200mm

Mute

9 mm Thickness

#### Color Options

Avola Mocha



1200x1200mm Mute 9 mm 4 Faces

02.3 Stone series 126 - 127

# Explore the unexplored



The strong and vivacious the Concrete series will be delight to explore as you must expect the unexpected.

Concrete series

**Lithic Latte** 

2400x1200mm

Concrete series

Lithic Nero

2400x1200mm



## Facade

A facade of a building is often the most important aspect from a design standpoint. With our latest technology and physical properties. Our products can be used on exterior facade and due to light weight helps in easy product installation.

Wall - Light Tiles

Lithic Latte

2400x1200mm *Mute* 

→ 6 mm Thickness


Wall - Dark Tiles

Lithic
Nero

2400x1200mm

Mute

→ 6 mm Thickness



#### Concrete series

### Lithic Latte


#### 2400x1200mm

#### Mute

→ 6 mm Thickness









Lithic Cacao







2400x1200mm 1200x1200mm Mute 6 mm, 9 mm 3 Faces

1200x1200mm

Mute

9 mm

4 Faces

2400x1200mm 1200x1200mm Mute 6 mm, 9 mm 3 Faces

2400x1200mm 1200x1200mm Mute 6 mm, 9 mm 3 Faces


2400x1200mm 1200x1200mm Mute 6 mm, 9 mm 3 Faces

1600x1600mm

Mute

9 mm

4 Faces



#### Concrete series

### **Exposed Cemento Fabrico Latte**

### 3200x1600mm

#### Mute

9 mm Thickness

12 mm Thickness

Total faces - 2



#### Color Options

**Exposed Cemento** Fabrico Antracite

**Exposed Cemento** Fabrico Bianco



3200x1600mm 1600x1600mm Mute 9 mm, 12 mm 2 Faces

3200x1600mm 1600x1600mm Mute 9 mm, 12 mm 2 Faces



## Relaxation Room

A serene and blissful enclosure, the relaxation room will be a cake walk, once you choose the subtle tile forms out of our eye-pleasing tile collection.

Wall - 1

Black Flash

3200x1600mm *Crystalline* 

→ 9 mm Thickness

Wall - 2

Black Fusion

3200x1600mm Crystalline

→ 9 mm Thickness

Floor

Cemento Antracite

1600x1600mm *Mute* 

→ 9 mm Thickness

Fire Area


Cemento Tortora

1600x1600mm *Mute* 

→ 9 mm Thickness



02.4 Concrete series 136 - 137



Wall - 2

Black Fusion

3200x1600mm Crystalline

→ 9 mm Thickness

Floor

Cemento Antracite

1600x1600mm *Mute* 

→ 9 mm Thickness



### Concrete series

### Cemento Beige

1600x1600mm

Mute

9 mm Thickness

Total faces - 4







#### Color Options

Cemento Bianco








1600x1600mm Mute 9 mm 4 Faces

1600x1600mm Mute 9 mm 4 Faces


1600x1600mm Mute 9 mm 4 Faces

02.4 Concrete series 138 - 139

# Explore the unexplored



Soft and delicate colour effect combined with spectacular opulence of the tile size comprises our exquisite range of onyx series.



## Business & Waiting Area

The manganous spread of your business and waiting area can be designed with the handpicked tiles from our fine range.

Wall - 1 Onice Bianco

2400x1200mm *Lustrous* 

→ 9 mm Thickness

Wall - 2 Seiser Coco

2400x1200mm *Mute* 

→ 9 mm Thickness

Floor

Seiser Coco

2400x1200mm *Mute* 

→ 9 mm Thickness



02.5 Onyx series 144 - 145



### Onyx series

### Onice Bianco

2400x1200mm

Lustrous

9 mm Thickness

Total faces - 3



Color Options

Onice Rosado



2400x1200mm Lustrous 9 mm 3 Faces



### Onyx series

### Graphite Onyx

2400x1200mm

Lustrous / Crystalline

9 mm Thickness

Total faces - 3



02.5 Onyx series 146 - 147



### Onyx series

### Fantasy Onyx

3200x1600mm

#### Crystalline

9 mm Thickness

12 mm Thickness







1600x1600mm Crystalline 9 mm 5 Faces



### Onyx series

## Honey Onyx

3200x1600mm

#### Crystalline

9 mm Thickness

12 mm Thickness

Total faces - 2






2400x1200mm Crystalline 9 mm, 12 mm 2 Faces



1600x1600mm Crystalline 9 mm, 12 mm 4 Faces

02.5 Onyx series 148 - 149

# Explore the unexplored



The slick and sophisticated. orgatech series is a treat for the eyes, slaying with its enlarged angles.





Hospitality

### Bar

The residential facade will stand strong with its length, take your pick from the luminous and arty style range of tiles to add beauty.

Wall

Twine Noir

2400x1200mm *Orgatech* 

→ 6 mm Thickness

Floor

Twine Noir

2400x1200mm *Orgatech* 

\chi 6 mm Thickness

Top Counter

Cava Antracite

3200x1600mm *Orgatech* 

 $\stackrel{\textstyle \star}{\textstyle \star}$  6 mm Thickness



### Orgatech series

## Twine Gris

2400x1200mm

Orgatech / Satin

→ 6 mm Thickness






#### Color Options

Twine Noir



2400x1200mm Orgatech / Satin 6 mm 3 Faces



### Orgatech series

### Foster Crema

2400x1200mm

Orgatech

9 mm Thickness

02.6 Orgatech series 156 - 157



### Orgatech series

### Grunge Copper

#### 3200x1600mm

#### Orgatech

★ 6 mm Thickness

9 mm Thickness

12 mm Thickness







2400x1200mm Orgatech 9 mm 2 Faces



### Orgatech series

### Rust Cotto

#### 3200x1600mm

#### Orgatech

→ 6 mm Thickness

12 mm Thickness


Total faces - 2





2400x1200mm Orgatech 6 mm, 9 mm, 12 mm 2 Faces

02.6 Orgatech series 158 - 159



Residential

### Bar

From refreshment space to party conversations has endless memories. The vintage look in tile that overjoyed everyones mood.

Wall

Keronix Smoke

2400x1200mm *Orgatech* 


→ 9 mm Thickness

Floor

Keronix Smoke

2400x1200mm *Orgatech* 

9 mm Thickness



### Orgatech series

### Keronix Smoke

2400x1200mm

#### Orgatech

9 mm Thickness

Total faces - 2




#### Color Options

Keronix Sand



2400x1200mm Orgatech 9 mm 2 Faces



### Orgatech series

### Iron Moss

#### 3200x1600mm

#### Orgatech

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

Total faces - 2



#### Color Options

Iron Corten


Iron Grey



3200x1600mm Orgatech 6 mm, 9 mm, 12 mm 2 Faces

3200x1600mm Orgatech 6 mm, 9 mm, 12 mm 2 Faces

02.6 Orgatech series 162 - 163



### Orgatech series

### Meta Moss

#### 3200x1600mm

#### Orgatech

★ 6 mm Thickness

9 mm Thickness

12 mm Thickness



2400x1200mm Orgatech 6 mm, 9 mm

#### Color Options

Meta Nero



3200x1600mm 2400x1200mm Orgatech 6 mm, 9 mm, 12 mm



### Orgatech series

### Ossido Ash

#### 3200x1600mm

#### Orgatech

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

#### Total faces - 2



#### Color Options

Ossido Blue



3200x1600mm Orgatech 6 mm, 9 mm, 12 mm 2 Faces

02.6 Orgatech series 164 - 165



### Black Bamboo

2400x1200mm

#### Orgatech / Satin

9 mm Thickness

12 mm Thickness

### Orgatech series



### Orgatech series

### Cava Antracite

### 3200x1600mm

#### Orgatech

→ 6 mm Thickness




12 mm Thickness





02.6 Orgatech series 166 - 167

# Explore the unexplored



Astonishingly mesmerising collection for the wilderness lovers.





# Florist Shop

The dreamy yet natural texture of our tile range will flawlessly blend into the colourful flower placements at the florist shop.

Wall

Timber Bianco

2400x1200mm *Mute* 

→ 6 mm Thickness

Floor

Timber Bianco

2400x1200mm *Mute* 

★ 6 mm Thickness

Counter Table

Cava Antracite

3200x1600mm *Orgatech* 

+ 6 mm Thickness





Wall Timber Bianco

2400x1200mm *Mute* 

★ 6 mm Thickness

Floor

Timber Bianco

2400x1200mm *Mute* 

→ 6 mm Thickness

Counter Table

Cava Antracite

3200x1600mm Orgatech

→ 6 mm Thickness



### Wooden series



2400x1200mm

Mute

→ 6 mm Thickness







Timber Silver Timber Bruno







2400x1200mm Mute 6 mm 3 Faces


2400x1200mm Mute 6 mm 3 Faces

02.7 Wooden series 174 - 175

# Explore the unexplored



Channelize the inner artist in you with our bold yet intricate art series, experience a world, never seen before.



Total faces - 2

### Art series

## Abstrato Moda

2400x1200mm

Crystalline

9 mm Thickness



### Art series

### Flora Mosaic


2400x1200mm

Lusterous

9 mm Thickness

02.8 Art series 178 - 179

# Explore the unexplored



The impeccably-clever designs available in our bookmatch will manifest a splendidly stunning interior decor style for your space.





Residential

## Kitchen

A classy and premium tile collection for the residential kitchen make your dreams come true, incorporating the functionality criteria as well.

Wall - Bookmatch

Calacutta Borghini

3200x1600mm Crystalline

 $\stackrel{\textstyle \star}{\longrightarrow}$  6 mm Thickness

Wall

#### Calacutta Borghini

1600x1600mm Crystalline

→ 9 mm Thickness

Floor

#### Calacutta Borghini

1600x1600mm Crystalline

→ 9 mm Thickness


Kitchen Platform

#### Carrara

2400x1200mm *Lustrous* 

+ 6 mm Thickness

02.9 Bookmatch 184 - 185



Wall

Calacutta Borghini

1600x1600mm *Crystalline* 

→ 9 mm Thickness

Floor

Calacutta Borghini

1600x1600mm *Crystalline* 


→ 9 mm Thickness

Kitchen Platform

Carrara

2400x1200mm *Lustrous* 

★ 6 mm Thickness



### Bookmatch

## Calacutta Borghini

#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness



12 mm Thickness

#### Bookmatch



Layout A

#### Bookmatch



Layout B

02.9 Bookmatch 186 - 187



2400x1200mm

Satin 6 mm, 9 mm Bookmatch Lustrous/ Satin

Lustrous / Crystalline /

#### Bookmatch

### Apuane Statuario

#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness



Layout A

Layout B

### Bookmatch

## Statuario Venetian

#### 2400x1200mm

#### Lustrous / Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness





Layout A

#### Bookmatch




Layout B

#### Bookmatch



#### Bookmatch



02.9 Bookmatch



#### Bookmatch

### Statuario Venato

#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

#### Bookmatch



Layout A

#### Bookmatch



Layout B

#### Bookmatch

## Statuario Platina

#### 3200x1600mm

#### Crystalline / Satin

→ 6 mm Thickness

9 mm Thickness

12 mm Thickness

#### Bookmatch



Layout A

#### Bookmatch



Layout B



02.9 Bookmatch 190 - 191

## Kitchen

Catering to the residential dining hall area, there are many tile design variants which can set new design trends with our contemporary styles.

Wall - Bookmatch

#### **Dolce Grey**

2400x1200mm *Lustrous* 



Wall - Dark

#### Pietra Grey


3200x1600mm *Satin* 



Kitchen Over Head

#### Statuario Venetian

2400x1200mm *Satin* 



Kitchen Platform Top

#### Statuario Venetian

2400x1200mm *Satin* 



Kitchen Platform Wall

#### **Dolce Grey**

2400x1200mm *Lustrous* 



→ 9 mm Thickness







Kitchen Island - Dark

Pietra Grey

3200x1600mm *Crystalline* 

🛨 6 mm Thickness

Kitchen Island - Light

Dolce Grey

2400x1200mm *Lustrous* 

关 6 mm Thickness

02.9 Bookmatch 194 - 195



### Bookmatch

## Dolce Grey

2400x1200mm

Lustrous

9 mm Thickness

#### Bookmatch



Layout A

#### Bookmatch



Layout B



### Bookmatch

### Breccia Blue

2400x1200mm

Lustrous

9 mm Thickness

#### Bookmatch



Layout A

#### Bookmatch



Layout B

02.9 Bookmatch 196 - 197



### Bookmatch

## Graphite Onyx

2400x1200mm

Lustrous / Crystalline


9 mm Thickness

#### Bookmatch



Layout A

#### Bookmatch



Layout B



### Bookmatch

### Flora Mosaic

2400x1200mm

Lustrous

9 mm Thickness

#### Bookmatch



Layout A

#### Bookmatch



Layout B


02.9 Bookmatch 198 - 199

# Explore the unexplored

kitchen countertop

Fullbody


12 mm Thickness



General Catalogue 2019 / '20

and hygienic tile quality take a step ahead.

200 - 201



### Meek Oyster

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness

Meek series

### Meek Mocha

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness



### Meek Corn

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness

### Meek series

### Meek Barista


3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness

02.10 Kitchen series 202 - 203



Meek series

## Meek Artic

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness

Meek series


### Meek Smoke

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness



### Meek Ash

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness



### Meek Umber

3200x1600mm


Crystalline / Satin

Fullbody

12 mm Thickness

Technoslab 02.10 Kitchen series 204 - 205

206 - 207



### Meek Walnut

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness

Meek series

### Meek Coal

3200x1600mm

Crystalline / Satin

Fullbody

12 mm Thickness

General

Technoslab


Catalogue 2019 / '20

### O3.1 Transportation & Handling


#### 03.1.1 Transporting TechnoSLAB

Following is a common slab storage situation; it highlights problems that can result from improper securing. The cargo transport unit of TechnoSLAB is formed on two "A - shaped" frames, provided by us. (Fig. 1 & 2)

Research into regulatory guidance from other sources did not uncover any recommendations specifically concerning natural stone slabs and road transportation, but the Swedish National Road and Transport Research (VTI) Institute issued recommendations for the transportation of panels more than 15 years ago, which are illustrated in (Fig. 3)



#### O3.1.2 Manually transporting a TechnoSLAB



Typical suction cups(Fig. 2) of different kinds are a prime aid, although a couple of workers will be needed to carry the tiles and these may still get deformed.

To allow the extraction of the slabs in a safe and easy way, it is recommended to position the pallets in a suitable area where the lift truck can be moved round all sides of the pallet.

In the case of tiles with a textured surface, soft rubber suction pads (Fig. 1) should be used to ensure a strong grip. Suction pads fixed to a lifting bar will make it easier to handle the products and prevent them from becoming deformed. By using two of these bars, all kind of operations can be performed by just two people.


However, the best solution is to use a rigid lifting frame (Fig. 3) with suction cups that grip the tile on all four sides.

The lifting frame can be designed to adapt to all tile formats, sizes or cut sections, keeping the tiles undamaged and allowing them to be handled by fewer people.

#### Possible operations

- 1. To remove the tiles from the box
- 2. To place them on the work table
- 3. To carry them anywhere on the work site
- 4. To spread cement-based adhesive on the underside
- 5. To help lay them

#### O3.1.3 Manually transporting a TechnoSLAB




### O3.2 Storage

Place the slabs length-wise on wooden beams to prevent the slabs from splintering.

4mm & 6mm slabs needs at least three support points, distributed evenly along the back of the slab; a full support is recommended. For example - an unused granite or marble slab with sufficient width. The best way to maintain the integrity of the slabs is to keep them in their original Packaging or use a full support on the back of the TechnoSLAB such as an unused granite or marble slab which is wide enough.

The supports must be able to hold the entire surface of the part during transport.

Too small supports may cause the part to break:



Avoid positioning large slabs against smaller slabs:

Technoslab 03 Technical 208 - 209


#### O3.3 Laying & Fixing


The growth in popularity of large format tiles, with their increased weight and smoother backs, presents new fixing challenges to the professional tiler.

Correct preparation of the subfloor or laying surface is crucial. The laying surface should be rigid, non-flexing and capable of supporting the expected load with minimal or no deflection. A level subfloor is extremely important in order to keep tiles from cracking. Sanding high spots and the use of a levelling compound on low spots is essential. It is also important that TechnoSLAB are clean and dry, if necessary wash them with clean water and dry them thoroughly before fixing.


Whatever your specific requirements, whether they be for standard or large format TechnoSLAB within internal or external applications, selecting the appropriate cement-based, fibre-reinforced or ready-mixed adhesive is vital to ensuring the success of your project.

Once your subfloor is clean and dry, spread the adhesive on the surface to be covered with a 10x10mm square toothed trowel, covering an area 5cm to 10cm more than the size of the TechnoSLAB. Always apply the adhesive in stripes running parallel with the short edge to remove air pockets and bubbles. By using this method, full coverage of the TechnoSLAB with adhesive is ensured.









Large format TechnoSLAB always require backbuttering. Back-buttering describes the process of applying a layer of adhesive to the back of the tiles using a trowel.

Using a specialist wheeled transport cart, fix the large format slab in a vertical position on the handling frame with the use of suction cups. Use a 10x10mm square toothed trowel for applying your adhesive to the wall or floor and when back-buttering use a 3x3mm square toothed trowel for the back of the tile.


Using the handling frame with suction cups, bring the slab into a vertical position and slowly lower it to horizontal. The TechnoSLAB should be firmly pressed into the adhesive along a straight edge, collapsing all adhesive ridges. Use a levelling system to avoid lippage and frequently checks that your TechnoSLAB are even using a suitable box level. Levelling systems are available with 2mm 3mm and 5mm tile spacers.

Periodically check the tiles backs to make sure there is full contact between the adhesive and tile. If not apply additional adhesive to the tile or use a troll with larger notches in your adhesive. As you are working wipe off excess mortar with a wet sponge.


### 03.4 Levelling

Tile levelling systems are now commonly used. With large-format TechnoSLAB, they are absolutely essential. Given the size of the TechnoSLAB and their slimline thickness, unless a levelling system is used, it will result in lippage.

After the first TechnoSLAB has been laid and levelled, before proceeding to lay the second one, insert levelling clips below the first (Fig. 2). Then lay the next TechnoSLAB and tap it to ensure a firm bond. Next, adjust the level(Fig. 3) of both TechnoSLABs by pushing the wedges into place 5 with the levelling pliers (Fig. 1).









The contributing factors to what causes TechnoSLAB lippage are how much warpage the TechnoSLAB has, the width of the grout, how flat the substrate is, and the expertise of the tile installer. We recommend that lippage should not be greater than 2mm at the most for this type of installation.

In order to ensure a uniform surface and produce a surface with acceptable lippage, make use a levelling system to avoid lippage and frequently check that your TechnoSLAB are even using a suitable box level. Levelling systems are available with 2mm, 3mm and 5mm tile spacers.







03 Technical 210 - 211

### 03.5 Cutting

Mark the portion to be removed at the ends of the TechnoSLAB with a pencil. Position the cutting guide with cutting carriage so that the references on the guide coincide with the lines marked on the panels. Lock the cutting guide with the cutting carriage in place using the suction cups. To guarantee correct scoring, the pressure and movement of the cutting carriage must be constant along the whole length of the cut. Score one end of the panel by 15cm pushing the cutting carriage towards the edge of the panel. Complete the scoring up to the opposite end of the panel.













Prepare the holes on all inner corners, minimum 3mm bit diameter.



When cutting a "U" shaped piece, mark and drill relief holes where the cut lines intersect, always making the shortest cut first.



When cutting an "L" countertop, drill relief holes where the cut lines intersect, always making the shortest cut first

### 03.6 Cleaning

#### 03.6.1 Cleaning after laying



We suggest a good initial cleaning after the laying on the floor or wall, this is very important for removing residual grouting and the normal dirt coming from the building works.

We suggest the use of a cementitious descaler, that is a lightly acid product that doesn't emit fumes that are harmful for the user and that can attack joints. In case of material layed with epoxy or resinous grouting, we recommend to clean after laying with specific detergent.

#### O3.6.2 Regular maintenance

Fig. 1



For a good cleaning of the floor we suggest the use of a natural detergent with a high cleaning power. In case of strong dirty and encrusted by the time, we recommend to consult the following scheme to find the perfect solution to every situation

TYPE OF DIRT	PRODUCT
Cement, Kalkstein, metal tracer, rust	Cementitious descaler
Residuals, stains and halos of epoxi joints	Epoxi descaler
Grease, tire marks, colours, marker, etc.	Non soap degrease
Grafitis	Acetone and antigraffiti star

#### O3.6.3 Recommendations

# Drying process

Once the tiles have been grouted and any excess grout cleaned off, it is important to wait the stipulated time before using the tiled surface; in other words, any cleaning should wait until the tiled surface is completely dry. We recommend waiting 5 days before cleaning in readiness for full use.

# Protection from liquid

The newly tiled surface must be protected from water and damp while the adhesive and grouting materials are maturing and hardening. This is particularly important in outside spaces and areas where there is a risk of freezing.

#### Damage Prevention

Measures should also be taken to protect the newly tiled surface against mechanical or chemical damage resulting from subsequent work by other professionals or later installations. Damage can be prevented by covering the floor tiles with thick cardboard or similar material.

# Cleaning products

For the final cleaning of the tiled surface, the products used should be compatible with the chemical resistance of the tiles. Avoid solid detergents with abrasive particles and solutions containing hydrofluoric acid, which attacks the glaze and causes irreversible damage to the ceramic tile.

03 Technical 212 - 213

### O3.7 Technical specification

CHARACTERISTIC	CHARACTERISTIC TEST METHOD		STD. AS PER ISO13006:2012/ EN14411 Gr.Bla	STD. AS PER IS15622:2017 Gr.Bla
Regulatory Properties				
Deviation in length and width	ISO 10545-2 & IS 13630-1	± 0.10 %	± 0.50 %	± 0.10 %
Deviation in thickness	ISO 10545-2 & IS 13630-1	± 4.00 %	± 5.00 %	± 5.0 %
Straightness in side	ISO 10545-2 & IS 13630-1	± 0.10 %	± 0.50 %	± 0.10 %
Rectangularity	ISO 10545-2 & IS 13630-1	± 0.10 %	± 0.60 %	± 0.10%
Surface flatness Central Curvature	ISO 10545-2 & IS 13630-1	± 0.10 %	± 0.50 %	± 0.50 %
Surface flatness Edge Curvature	ISO 10545-2 & IS 13630-1	± 0.10 %	± 0.50 %	± 0.50 %
Surface flatness Warpage	ISO 10545-2 & IS 13630-1	± 0.10 %	± 0.50 %	± 0.50 %
Surface Quality	ISO 10545-2 & IS 13630-1	> 95% defects free	> 95% defects free	> 95% defects free
Small Color Difference	ISO 10545-16	No Change	Unaltered	N.A.
Glossiness (With Nano Polished)	Gloss Meter 60°	> 90° **	As per Mfg.	As per Mfg.
Glossiness (Without Polished)	Gloss Meter 60°	7° < Gloss < 14°**	As per Mfg.	As per Mfg.
Glossiness (Satin Finished)	Gloss Meter 60°	15° < Gloss < 25°**	As per Mfg.	As per Mfg.
Structural Properties				
Water absorption	ISO 10545-2 & IS 13630-3	<b>≤ 0.50 %</b>	≤ 0.50 %	≤ 0.80 %
Bulk density	DIN51082 & IS 13630-3	> 2.28 gm/cc	> 2.00 g/cc	Min. 2.20 g/cc
Duik derisity	7 DINSTOOL & 13 13030-3	7 2.20 gn/cc	7 2.00 g/cc	141111. 2.20 g.cc
Massive Mechanical Properties				
Modulus of rupture	ISO 10545-4 & IS 13630-6	Min. 37.0 N/mm²	Min. 35.0 N/mm²	Min. 35.0 N/mm²
Breaking strength thickness <7.5	ISO 10545-4 & IS 13630-6	Min. 1000.0 N	Min. 700.0 N	Min. 700.0 N
Breaking strength thickness ≥7.5	ISO 10545-4 & IS 13630-6	Min. 1600.0 N	Min. 1300.0 N	Min. 1100.0 N
Surface Mechanical Properties				
MOH'S hardness	EN 101 & IS 13630-13	Min. 4***	Min. 4	Min. 5
Surface abrasion resistance-Glossy #	ISO 10545-7 & IS 13630-11	Min. Class 2	As per Mfg.	Min. Class II
Surface abrasion resistance-Matt #	ISO 10545-7 & IS 13630-11	Min. Class 3	As per Mfg.	Min. Class II
Thermal Hydrometric Properties				
Moisture expansion	ISO 10545-10 & IS 13630-3	NIL	Max. 0.06	Max. 0.02
Thermal expansion(COE) at 100°C	ISO 10545-8 & IS 13630-4	Max. 6.0 x 10 <sup>-6</sup>	As per Mfg.	Max. 7.0 x 10 <sup>-6</sup>
Thermal shock resistance	ISO 10545-9 & IS 13630-5	Min. 10 Cycle	Min. 10 Cycle	Min. 10 Cycle
Crazing Resistance at 7.5 Bar	ISO10545-11 & IS 13630-9	Min. 6 Cycle	As per Mfg.	Min. 4 Cycle
Impact resistance(COR)	ISO 10545-5 & IS 13630-14	Min. 0.55	As per Mfg.	Min. 0.55
Frost resistance	ISO10545-12 & IS 13630-10	Frost Proof	As per Mfg.	As per Mfg.
Chemical Properties				
**Resistance to Staining Glazed	ICO 10E 4E 14 0 IC 12620 0	Min Class 4/Min Class I	Min. Class 3	Min. Class I
**Resistance to Staining Glazed	ISO 10545-14 & IS 13630-8 ISO 10545-13 & IS 13630-8	Min. Class 4 / Min. Class I Min. Class GA / Min. Class AA		
icals & Swimming Pool Salts Glazed	150 10545-13 & 15 13630-8		Min. Class GB	Min. Class AA
**Resistance to Low / High Concentrate Acid and Alkalis Glazed	ISO 10545-13 & IS 13630-8	Min. Class GLB"" / Min. Class A""	As per Mfg.	As per Mfg.
Safety Properties				
Skid resistance(DCOF-DRY)	ISO 10545-17	→ 0.40	As per Mfg.	As per Mfg.
Slip resistance(DCOF)( R value )##	ISO 10545-17	N.A.	As per Mfg.	As per Mfg.
Determination of Lead & Cadmium Release for Glazed Tiles	ISO 10545-15	Dose not yield Pb & Cd	As per Mfg.	N.A.
Fire Resistance	N.A.	Fire Proof	As per Mfg.	As per Mfg.

<sup>#</sup> Glaze tiles Intended for use on floor

### O3.8 Container packing details

	Size	Thickness	Weight /Slab	No. of Bundles or A-Frames	Total Slabs or Box	Slabs / Container	sq mtr / Container	Weight/ Container	Size of Container
**	3200x1600mm	6mm	73.5 kg	7	40 slabs	280	1433.60	21.5 t	20 ft
##	3200x1600mm	6mm	73.5 kg	3	40 slabs	120	614.40	9.82 t	20 ft
##	3200x1600mm	6mm	73.5 kg	9	40 slabs	360	1843.20	27.6 t	40 ft
**	3200x1600mm	9mm	110.0 kg	7	26 slabs	182	931.84	20.2 t	20 ft
##	3200x1600mm	9mm	110.0 kg	9	26 slabs	234	1198.08	25.7 t	40 ft
**	3200x1600mm	12mm	147.0 kg	7	20 slabs	140	716.80	21.5 t	20 ft
##	3200x1600mm	12mm	147.0 kg	3	20 slabs	60	307.20	9.8 t	20 ft
##	3200x1600mm	12mm	147.0 kg	9	20 slabs	180	921.60	27.4 t	40 ft
* + #	2400x1200mm	6mm	41.5 kg	8° + 4#	56° + 24″	544	1566.72	23.0 t	20 ft
##	2400x1200mm	6mm	41.5 kg	4	40 box	320	921.60	14.0 t	20 ft
#	2400x1200mm	6mm	41.5 kg	12	24 slabs	288	829.40	13.1 t	20 ft
*	2400x1200mm	6mm	41.5 kg	11" + 1"	56' + 24'	640	1843.20	27.0 t	40 ft
##	2400x1200mm	6mm	41.5 kg	8	80 slabs	640	1843.20	27.0 t	40 ft
#	2400x1200mm	6mm	41.5 kg	24	24 slabs	576	1658.90	26.3 t	40 ft
* + #	2400x1200mm	9mm	62 kg	8* + 4#	34" + 16#	336	967.68	21.4 t	20 ft
##	2400x1200mm	9mm	62 kg	4	50 box	200	576.00	12.8 t	20 ft
#	2400x1200mm	9mm	62 kg	12	16 slabs	192	552.90	13.1 t	20 ft
*	2400x1200mm	9mm	62 kg	12" + 1"	34° + 12° box	420	1209.6	26.5 t	40 ft
##	2400x1200mm	9mm	62 kg	8	50 box	400	1152.00	25.4 t	40 ft
#	2400x1200mm	9mm	62 kg	24	16 slabs	384	1105.90	26.2 t	40 ft
##	1600x1600mm	9mm	55 kg	6	48 slabs	288	737.28	17.0 t	20 ft
##	1600x1600mm	9mm	55 kg	11	48 slabs	528	1351.68	27.2 t	40 ft
* + #	1200x1200mm	9mm	62 kg	13' + 4"	26' + 21"	422	1215.36	27.0 t	20 ft
#	1200x1200mm	9mm	62 kg	17	26 slabs	422	1215.36	27.0 t	40 ft

<sup>\*\* =</sup> Bundle | \* = Vertical Pallet | ## = A-Frame | # = Horizontal Crate

#### Note:

03 Technical 214 - 215

<sup>##</sup> As per customer requirement

<sup>\*\*</sup> Glossiness 90% with nano technology

<sup>\*\*\*</sup> Without nano technology (Unpolished Vitrified tiles)

\*\*\*\* Except Hydrofluoric Acid & it's compound

<sup>1.</sup> Horizontal Crates: Slabs will be available without box packing for horizontal crates.

<sup>2. 3200</sup>x1600mm: will be available without box packing only.

<sup>3. 2400</sup>x1200mm: 6mm thickness slabs available in 2 pcs box packing & 9mm thickness slabs available in 1 pcs box packing.

<sup>4. 1600</sup>x1600mm: 9mm thickness slabs available in 1 pcs box packing.

<sup>5. 1200</sup>x1200mm: 9mm thickness slabs available in 2 pcs box packing.